

SCH5900 Series / Grade 1 / Rim Exit Devices

SCH5910S Panic-Rated Rim Exit Device / For wide stile and flush doors use

SCH5910F Fire-Rated Rim Exit Device / For wide stile fire labeled doors use



Application

- For use on single doors or double doors with mullion (Fire rated device must use on 4' x 8' single or 8' x 8' double fire labeled doors).
- Fits for 1 3/4" (44mm) thick standard RHR or LHR hollow metal doors & wood doors, other than standard 1 3/4" is available but specify door thickness when ordered.
- Minimum Stile width: 3 1/2" (90mm).

SCH531 Strike Shim



Furnished with SCH532 strike together. This shim is 1/8" thick for prepare doors with 1/2" stop, it is used to obtain correct distance between the device latch and the surface applied strike when the stop is 1/2" high. If the frame has 5/8" stop, then this shim is unnecessary.
Steel Plated.

SCH532 Panic Rim strike

Surface applied. Standard on SCH5000

Series panic rim exit devices.
Stainless Steel, With a plated roller.



SCH533 Fire Rim Strike

Surface applied. Standard on SCH5000

Series fire rim devices. It is 100% stainless steel including a roller

Specifications

Device Head Cover----	Stainless steel, non-ferrous alloy
Chassis -----	Steel, plated
Mechanism Housing----	Steel, or stainless steel
Push Bar -----	Steel, or stainless steel
End Cap-----	Steel, or stainless steel
Latch Bolt -----	100% stainless steel, deadlocking type, 11/16" (17mm) throw
Deadlocking Latch ----	100% stainless steel 5/8"(16mm) throw
Strikes -----	SCH533 Rim (fire rated) SCH531&SCH532 Rim (panic rated)
Handing-----	Non-handed
Mounting Fasteners----	Machine screws furnished standard, Sex Nut and Bolt (SNB) are required to use for wood doors. Order SNB separately.
Dogging* -----	Hex key dogging standard (Allen-type key furnished)
Dogging Options -----	Cylinder dogging or Less dogging, See page 64
Finish -----	605, 630, 689, 690, four finishes
Dimension -----	See page 60
Device Length -----	See page 60
UL Listed -----	For Panic Hardware (original listed model no.: SCH500SA) For fire Exit Hardware (original listed model no.: SCH500AF)

*Fire rated rim device has no mechanical dogging.
(Dogging device is not permitted on fire-rated exit device)