GRADE 1 MORTISE LOCKSETS

SCHM Series Mechanical Lockset / Grade 1

Our heavy-duty mortise locks meet ANSI/BHMA 156.13 Grade 1 standards, ensuring maximum security and durability. All locks are field reversible and can be rehanded easily without disassembly, making installation quick and efficient.

Features:

- Reversible Without Disassembly
 - Simplifies installation by allowing easy handing changes.
- Retrofits Other Brand Locksets
 - Compatible with various lock brands

(consult factory for details).


- Vandal-Resistant Clutch
 - Protects against forced entry and unauthorized operation.

Finishes Available:

- PB Polished Brass
- SN Satin Nickel
- SC Satin Chrome
- CR Polished Chrome
- ORB Oil Rubbed Bronze
- PVD Lifetime Finish



ANSI Function Diagram



| Armored Front | 1 ¼" x 8" x 7/32" (32 mm x 203 mm x 6 mm) standard. | | |
|-----------------|---|--|--|
| Backset | 2 ¾" (70 mm) standard. | | |
| Bolts | 3/4" (19 mm) throw stainless steel latch with anti-friction tongue. 1" (25 mm) throw stainless steel dead bolt. | | |
| Case | 3 15/16" x 6 1/16" x 29/32" (100 mm x 154 mm x 23 mm). | | |
| Clutch | Internal clutch mechanism provides vandal resistance by allowing lever rotation to retract the latch even when locked. | | |
| Cylinder & Keys | 1 1/8" (28.58 mm) 6 pin cylinder with 'C' type keyway. | | |
| Door Thickness | Standard for use on 1 ¾" (44 mm) thick door standard. Specify thickness if if different from standard, up to 2 ¼" (57.15 mm) thick door. | | |
| Handing | SCHM Series locks are field reversible without disassembly. | | |
| I-Core | Compatible with interchangeable core cylinders from other manufacturers. | | |
| Levers | Forged brass or bronze and cast stainless steel for durability. | | |
| Rose | Heavy wrought reinforced brass, bronze, and stainless steel. | | |
| Spring Cages | Heavy-duty spring cages included as needed for function. | | |
| Strike | ANSI curved lip strike 1 $\frac{1}{4}$ " x 4 $\frac{7}{8}$ " x 1 $\frac{3}{16}$ " (32 mm x 123.83 mm x 30 mm) lip-to-center and dust box. | | |

Tel: (888) 463-1194 Email: info@schproducts.com Fax: (888) 990-0998 Website: schproducts.com

GRADE 1 MORTISE LOCKSETS

SCHM Series Ordering Information / Grade 1 / Mortise Locksets

| 4 | SCHM1001 | F01 | Passage – Latch bolt retracted by lever from either side at all times. |
|------|----------|-------------------|--|
| | SCHM3004 | F04 | Office – Latch bolt operated by lever from either side except when outside lever is made inoperative by key outside or by turning inside thumb turn. When outside lever is locked, latch bolt is retracted by key from outside or by operating inside lever. Outside lever remains locked until thumb turn is return to vertical position or unlock by key. Auxiliary latch deadlocks latch bolt when doors closed. |
| | SCHM2005 | F05 | Classroom – Latch bolt retracted by lever from either side unless outside is locked by key. Unlocked from outside by key. Inside lever always free for immediate exit Auxiliary latch deadlocks latch bolt when door is closed. |
| داًے | SCHM2007 | F07 | Storeroom – Latch bolt is retracted by a key from the outside or by the knob/lever from the inside. Outside lever always inoperative. Auxiliary latch deadlocks latch bolt when door is closed. |
| | SCHM2009 | F09 | Apartment Entrance Vestibule – Latch bolt operated by lever from either side except when outside lever is locked by key from inside. When outside lever is locked, latch bolt is retracted by key from outside or by operating Inside lever. Auxiliary dead latch. |
| | SCHM2413 | F13 | Corridor / Exit – Latch bolt operated by lever from either side. Dead bolt projected by key from outside and turn from inside. Operating inside lever retracts both bolts and unlocks outside. |
| 4 | SCHM3420 | F20 | Entrance – Latch bolt operated by lever from either side, except when outside lever is made inoperative by toggle button. Dead bolt operated by key outside or turn inside. Key outside operates both bolts. Operating inside lever retracts both bolts and outside remains locked. Latch bolt is deadlocked when outside lever is made inoperative or when the dead bolt is projected. When dead bolt Is retracted, lever is unlocked by toggle button. |
| | SCHM1022 | F02 F04 F22 | Privacy – Latch bolt operated by lever from either side except when outside lever is locked by inside thumb turn. Operating inside lever, closing door or operating outside emergency release unlocks outside lever. |
| 4 | SCHM0071 | | Single Dummy Trim – Lever on one side fixed by mounting bar. |
| 47 | SCHM0072 | | Double Dummy Trim – Levers on both sides are fixed using a mounting bar. |
| 4 | SCHM0075 | | Single Dummy Trim – Lever on one side fixed. Includes lock chassis and armor front. |
| 4 | SCHM0078 | | Double Dummy Trim – Lever on both sides. Includes lock chassis and armor front. |

Tel: (888) 463-1194 Email: info@schproducts.com Fax: (888) 990-0998 Website: schproducts.com

GRADE 1 MORTISE LOCKSETS

SCHM Series Options / Grade 1 / Mortise Locksets

Functions

SCHM1001 Passage

SCHM3004 Office

SCHM2005 Classroom

SCHM2007 Storeroom

SCHM2009 Apartment Entrance / Vestibule

SCHM2413 Corridor / Exit

SCHM3420 Entrance

SCHM1022 Privacy

SCHM0071 Single Dummy Trim

SCHM0072 Double Dummy Trim

SCHM0075 Single Dummy Trimwith Chassis

SCHM0076 Double Dummy Trim Chassis

Handing

L Left hand LR Left hand reversed R Left hand RR Right hand reversed

Finish

630 Dull Stainless (Standard)

605 Bright Brass

606 Dull Brass

611 Bright Bronze

612 Dull Bronze

613 Oil Rubbed Bronze

625 Bright Chrome

626 Dull Chrome

629 Bright Stainless Steel

SCHM Series locksets retrofit the following existing door preps of the following lock brands with rose or escutcheon trim.

Knob or lever trim mounting holes only may require relocation. See SCHM template.

Schlage

Lawrence

- Hager
- MarksSargent

- Corbin
- Dorma


Cal-Royal

Arrow

SCHM Series locksets retrofits the following existing door preps of the following lock brands with escutcheon trim only.

Minor modification to the key cylinder hole position is required, and trim mounting holes may need to be relocated. See SCHM template.

- Falcon
- Yale
- PDQ



Key Cylinder - Optional

CYL-6KDQ

6 pins, 1.125" mortise cylinder, keyed different, dull chrome

CYL-6KAQ

6 pins, 1.125" mortise cylinder, keyed alike, dull chrome

Tel: (888) 463-1194 Email: info@: Fax: (888) 990-0998 Website: sch

Email: info@schproducts.com Website: schproducts.com