

# GRADE 1 SURFACE VERTICAL ROD EXIT DEVICES

## SCH5900 Series / Grade 1 / SVR Exit Devices

**SCH5930S:** Panic-Rated SVR Exit Device / For wide stile exit doors use

**SCH5930F** Fire-Rated SVR Exit Device / For wide stile fire labeled doors use

### Applications

- For use on all single doors or double doors where two-point latch is desirable (inactive) leaf of double door in specialty). (Fire rated device must use on 4' x 8' (1219.2mm x 2438.4mm) single or 8' x 8' (2438.4mm x 2438.4mm) double fire labeled doors).
- Fits for 1 3/4" (44 mm) thick standard RHR or LHR hollow metal doors & wood doors, other than standard 1 3/4" is available but specify door thickness when ordered.
- Minimum Stile width: 3 1/2" (90 mm).

These SVR models cannot be omitted the bottom rod to use as Less Bottom Rod (LBR) devices. If LBR is desired, it must be re-tested & approved by a nationally recognized test laboratory.



### SCH534 Top Strike

Applied to surface of stop.  
Hardened steel, plated



### SCH537 Bottom Strike

Applied to surface of floor.  
Nonferrous alloy, plated



### Specifications

<b>Device Head Cover</b>	Steel, stainless steel, or nonferrous alloy	<b>Handing</b>	Non-handed
<b>Chassis</b>	Steel, plated	<b>Mounting Fasteners</b>	Machine screws furnished standard, Sex Nut and Bolt (SNB) are required to use for wood doors. Order SNB separately.
<b>Mechanism Housing</b>	Steel, stainless steel	<b>Dogging</b>	Hex key dogging standard Less dogging. See page 64
<b>Push Bar</b>	Steel, stainless steel	<b>Finish</b>	605, 630, 689, 690, four finishes
<b>End Cap</b>	Steel, stainless steel	<b>Dimension</b>	See page 60
<b>Latch Bolt</b>	100% stainless steel, 1/2" (13 mm) throw	<b>Device Length</b>	See page 60
<b>Latch Case Covers</b>	Steel, stainless steel	<b>UL Listed</b>	For Panic Hardware (original Listed modes no.: SCH5000)
<b>Vertical Rods</b>	Tubular aluminum with rod guide		

\* Fire rated SVR device has no mechanical dogging. (Dogging device is not permitted on fire-rated exit device)